

Water4 Dairy

Legacy II-ss60m

Ozone Water Treatment Technology

Raising the bar in dairy water treatment performance



email: info@water4dairy.com

phone: 780-999-1906

Water4 Dairy

Benefits and Specifications

Legacy II-ss60m

Product Information and Specifications

- On board 93% +/- 3% 30 scfh (14 lpm) @ 10
 psig oxygen concentrator
- Ozone output 60.0 grams per hour @ 30 scfh 5.0% concentration by weight
- System information and diagnostics (sid) lcd display
- Self resonating ozone generation reaction chamber
- CSA certified time delay enclosure and control panel
- 120 gal mass transfer micro-bubbling contact tank
- Available in 0 30 gpm flow rates
- Adjustable mazzie manifold with pre/post pressure gauges
- Schd 80 plumbing
- Ozone destruct unit with j valve
- 2 hp stainless Gould recirculation booster pump

System customized to your dairy's infrastructure


- Water is treated when you need it
- Reduces system footprint due to no onsite water storage requirements
- System plugs into your existing water infrastructure minimizing onsite installation costs

Water4 Dairy OZONE WATER SYSTEMS



Optimizing your dairy's productivity

- Improve milk production & butterfat content
- Stabilize water quality to your herd
- Improve animal and overall herd health due to better hydration
- Improve performance from water related dairy equipment and infrastructure such as water lines and robots
 - No ongoing chemical costs



648

Service Re	equirements (Legacy II ss-60m)	Unit width	Length	Height
Electrical	230V / 20A	Standard Metric	Standard Metric	Standard Metric
Water	0 - 30 gpm max	60inch 150cm	64inch 160cm	80inch 200cm
Ozone	60 grams/hour @ 30 scfh oxygen			